DATE and TIME	COURSE			SUBJECT	
14-07-2018 2.30 p.m. to 4.30 p.m.	cou	M.Tech/Marses offer/UVCE/U	ed by	CHEMICAL ENGINEERING	
MAXIMUM MARKS	TOTAL D	URATION	MAXIMUN	M TIME FOR ANSWERING	
100	150 Mi	inutes	120 Minutes		
MENTION YOUR PO	CET NO.	QUESTION BOOKLET DETAILS		OOKLET DETAILS	
		VERSION	CODE	SERIAL NUMBER	
		A		105065	

DOs:

- Candidate must verify that the PGCET number & Name printed on the OMR Answer Sheet is tallying with the PGCET number and Name printed on the Admission Ticket. Discrepancy if any, report to invigilator.
- 2. This question booklet is issued to you by the invigilator after the 2nd bell i.e., after 2.25 p.m.
- The Version Code of this Question Booklet should be entered on the OMR Answer Sheet and the respective circle should also be shaded completely.
- 4. The Version Code and Serial Number of this question booklet should be entered on the Nominal Roll without any mistakes.
- 5. Compulsorily sign at the bottom portion of the OMR answer sheet in the space provided.

DON'Ts:

- 1. The timing and marks printed on the OMR answer sheet should not be damaged / mutilated / spoiled.
- 2. The 3rd Bell rings at 2.30 p.m., till then;
 - Do not remove the paper seal / polythene bag present on the right hand side of this question booklet.
 - · Do not look inside this question booklet.
 - Do not start answering on the OMR answer sheet.

IMPORTANT INSTRUCTIONS TO CANDIDATES

- This question booklet contains 75 (items) questions and each question will have one statement and four answers. (Four different options / responses.)
- After the 3rd Bell is rung at 2.30 p.m., remove the paper seal / polythene bag on the right hand side of this
 question booklet and check that this booklet does not have any unprinted or torn or missing pages or items etc.,
 if so, get it replaced by a complete test booklet. Read each item and start answering on the OMR answer sheet.
- 3. During the subsequent 120 minutes:
 - · Read each question (item) carefully.
 - Choose one correct answer from out of the four available responses (options / choices) given under
 each question / item. In case you feel that there is more than one correct response, mark the response
 which you consider the best. In any case, choose only one response for each item.
 - Completely darken / shade the relevant circle with a BLUE OR BLACK INK BALL POINT PEN
 against the question number on the OMR answer sheet.

ಸರಿಯಾದ ಕ್ರಮ	ತಪ್ಪ ಕ್ರಮಗಳು WRONG METHODS
CORRECT METHOD	\bigcirc
A • C D	② B C D A B C ② A ● ● D A B C D

- Use the space provided on each page of the question booklet for Rough Work. Do not use the OMR answer sheet for the same.
- After the last Bell is rung at 4.30 p.m., stop marking on the OMR answer sheet and affix your left hand thumb impression on the OMR answer sheet as per the instructions.
- Handover the OMR ANSWER SHEET to the room invigilator as it is.
- After separating the top sheet (KEA copy), the invigilator will return the bottom sheet replica (Candidate's copy) to you to carry home for self-evaluation.
- 8. Preserve the replica of the OMR answer sheet for a minimum period of ONE year.
- 9. Only Non-programmable calculators are allowed.

Marks Distribution

PART-1 : 50 QUESTIONS CARRY ONE MARK EACH (1 TO 50)
PART-2 : 25 QUESTIONS CARRY TWO MARKS EACH (51 TO 75)

CH-A



	TETTER WEST	

A 2 CH

CHEMICAL ENGINEERING PART – 1

(Each question carries one mark.)

 $(50\times1=50)$

	[일반] [인터 보고 있다고 있다고 다음 살이 보니 되는데 되었다. [1] [1] [1] [1]		
1.	Distillation is a separating process based on of liquid mixture.	4.	For an endothermic reaction, the minimum value of energy of activation
	(A) Vaporizing		will be (where, $\Delta H = \text{enthalpy of the}$
	(B) Condensation		reaction)
	(C) Freezing		(A) ΔH
	(D) None of these		(B) > ΔH
			(C) < ΔH
2.	Unit of mass velocity:		(D) 0
	(A) kg/m.hr		Annual Annual India
	(B) kg/m ² .hr	5.	The reverse process of fractional crystalisation is called
	(C) kg/hr		(A) Stripping
	(D) kg/m ²		(B) Leaching
			(C) Differential distillation
3.	In a binary liquid system, the		(D) Absorption
	composition expressed as		
	is independent of the temperature & pressure. (A) kg of solute/kg of solvent		Which of the following factors does not contribute to the pressure drop in a
			pipeline?
	(B) kg-mole of solute/kg-mole of		(A) Velocity of fluid
	solvent		(B) Size of pipe
	(C) kg-mole of solute/1000 kg of solvent		(C) Length of pipe and number of bends
	(D) All (A), (B) & (C)		(D) None of these

Space For Rough Work

3

- 7. Which of the following can be used to create a flow of gas, where no significant compression is required?
 - (A) Reciprocating compressor
 - (B) Blower
 - (C) Axial flow compressor
 - (D) Centrifugal compressor
- 8. Gear pump
 - (A) is a positive displacement pump.
 - (B) is a centrifugal pump.
 - (C) is a non-positive displacement pump.
 - (D) can be started with delivery valve closed.
- The speed of sound in an ideal gas varies as the
 - (A) Temperature
 - (B) Pressure
 - (C) None of these
 - (D) Density

- The Navier-Stokes equation deals with the law of conservation of
 - (A) Mass
 - (B) Energy
 - (C) Both (A) & (B)
 - (D) Momentum
- Cyclones are used primarily for separating
 - (A) Solids
 - (B) Solids from fluids
 - (C) Liquids
 - (D) Solids from solids
- 12. The main differentiation factor between tube mill and ball mill is the
 - (A) Length to diameter ratio
 - (B) Size of the grinding media
 - (C) Final product size
 - (D) Operating speed

- 13. Fick's law relates to
 - (A) Energy consumption
 - (B) Final particle size
 - (C) Feed size
 - (D) None of these
- **14.** Which is a secondary crusher for a hard and tough stone?
 - (A) Jaw crusher
 - (B) Cone crusher
 - (C) Impact crusher
 - (D) Toothed roll crusher
- 15. Carbon black is pulverised in a
 - (A) Hammer crusher
 - (B) Ball mill
 - (C) Roll crusher
 - (D) Gyratory crusher

- 16. In a forward feed multiple effect evaporators, the pressure is
 - (A) Highest in last effect
 - (B) Lowest in last effect
 - (C) Same in all effects
 - (D) Dependent on the number of effects
- 17. For the same heat load and mass flow rate in the tube side of a shell and tube heat exchanger, one may use multipass on the tube side, because it
 - (A) Decreases the pressure drop
 - (B) Decreases the outlet temperature of cooling medium
 - (C) Increases the overall heat transfer co-efficient
 - (D) None of these
- 18. LMTD can't be used as such without a correction factor for the
 - (A) Multipass heat exchanger
 - (B) Baffled heat exchanger
 - (C) Condensation of mixed vapour in a condenser
 - (D) All (A), (B) and (C)

19.	Evaporator tubes are generally	22.	For spontaneous changes in an isolated system (S = entropy)
	(A) Horizontal		(A) $dS = 0$
	(B) Vertical (C) Inclined		(B) dS < 0
	(D) Random		(C) dS > 0
			(D) dS = Constant
20.	Circulation pump is located below the evaporator to	23.	For equilibrium process (i.e. reversible) in an isolated system
	(A) Avoid cavitation		(A) $dS = 0$
	(B) Avoid frequent priming		(B) dS < 0
	(C) Create more suction head		(C) dS > 0
	(D) None of these		(D) dS = Constant
21.	Entropy is a measure of the of a system.		The four properties of a system viz. P, V, T, S are related by
	(A) Disorder		equation. (A) Gibbs-Duhem
	(B) Orderly behaviour		(B) Gibbs-Helmholtz
	(C) Temperature changes only		(C) Maxwell's

(D) None of these

(D) None of these

- 25. Any substance above its critical temperature exists as
 - (A) Saturated vapour
 - (B) Solid
 - (C) Gas
 - (D) Liquid
- **26.** Molecular weight of polymers are in the range of
 - (A) $10 \text{ to } 10^3$
 - (B) 10^2 to 10^7
 - (C) 10^7 to 10^9
 - (D) 109 to 1011
- 27. Thermoplastic materials
 - (A) do not soften on application of heat.
 - (B) are heavily branched molecules.
 - (C) are solvent insoluble.
 - (D) None of these

- 28. Vulcanisation of rubber
 - (A) decreases its tensile strength.
 - (B) increases its ozone & oxygen reactivity.
 - (C) increases its oil & solvent resistance.
 - (D) converts its plasticity into elasticity.
- 29. Thermosetting materials
 - (A) are cross-linked molecules.
 - (B) soften on application of heat.
 - (C) are solvent soluble.
 - (D) None of these
- 30. Most commonly used rubber vulcanisation agent is
 - (A) Sulphur
 - (B) Bromine
 - (C) Platinum
 - (D) Alumina

- 31. BET apparatus is used to determine the
 - (A) specific surface of a porous catalyst
 - (B) pore size distribution
 - (C) pore diameter
 - (D) porosity of the catalyst bed
- 32. The optimum performance for reactors operating in parallel is obtained when the feed stream is distributed in such a way, that the
 - (A) space time for each parallel line is same
 - (B) space time for parallel lines is different
 - (C) larger reactors have more space time compared to smaller ones
 - (D) None of these
- 33. Back mixing is most predominant in
 - (A) a well stirred batch reactor
 - (B) a plug-flow reactor
 - (C) a single CSTR
 - (D) CSTR's connected in series

- 34. The ratio of moles of a reactant converted into the desired product to that converted into unwanted product is called
 - (A) Operational yield
 - (B) Relative yield
 - (C) Selectivity
 - (D) None of these
- 35. The performance of a cascade of CSTR's can be improved by adding
 - (A) P.F. reactor in series
 - (B) P.F. reactor in parallel
 - (C) More CSTR's in series
 - (D) More CSTR's in parallel
- 36. Temperature rise in the bomb calorimeter is usually measured by a thermometer.
 - (A) Beckman
 - (B) Bimetallic
 - (C) Platinum resistance
 - (D) Vapor pressure

- Humidity is most commonly measured by
 - (A) partial vapor pressure determination
 - (B) dry and wet bulb temperature measurement
 - (C) physical expansion
 - (D) evaporation
- 38. Working of a constant volume gas thermometer is based on the
 - (A) Archimedes principle
 - (B) Pascal's law
 - (C) Charle's law
 - (D) Boyle's law
- 39. Bolometer measures the
 - (A) Current
 - (B) Temperature
 - (C) Flow rate
 - (D) Millivolts
- 40. Choose the one whose resistance decreases with increase in temperature.
 - (A) Platinum
 - (B) Carbon
 - (C) Constantan
 - (D) Aluminum

- 41. Which one of the following is not an elastomer?
 - (A) Polyisoprene
 - (B) Neoprene
 - (C) Nitrile-butadiene
 - (D) None of these
- **42.** Styrene-butadiene-rubber (SBR) as compared to natural rubber has
 - (A) poorer tensile strength.
 - (B) poorer resistance to oxidation
 - (C) greater amount of heat build-up under heavy loading.
 - (D) All (A), (B) and (C)
- 43. Pick out the wrong statement.
 - (A) Cold rubber (SBR) is superior as compared to hot rubber (SBR).
 - (B) Polymerisation temperature can modify the properties of SBR.
 - (C) Production of cold SBR employs lower pressure as compared to that of hot SBR.
 - (D) None of these
- 44. The process involved in converting rubber into a thin sheet or coating it on fabric is called
 - (A) Extrusion
 - (B) Mastication
 - (C) Calendering
 - (D) Vulcanization

45.	Flexible foam for mattresses is usually	48.	Separation of two or more components
	made of		of a liquid solution cannot be achieved
	(A) PVC		by (A) Absorption
	(B) Silicone		(A) Absorption (B) Evaporation
	(C) Polyurethanes		(C) Liquid extraction
	(D) Polyamides		(D) Fractional crystallization
46.	Unit of molal diffusivity is	49.	In batch distillation with constant
	(A) cm ² /sec gm. mole		reflux, overhead product composition with time.
	(B) gm moles/cm ² . sec		(A) increase
	(C) gm moles/cm. sec		(B) decrease
	(D) gm moles/cm ² . sec ²		(C) may increase or decrease, depend on the system
			(D) does not vary
47.	If R _m is the minimum reflex ratio, the optimum reflux ratio may be around		
	R _m	50.	An azeotropic mixture is a
			mixture.
	(A) 1.2 to 1.5		(A) Binary
	(B) 2.5 to 3		(B) Ternary
	(C) 3 to 4		(C) Constant boiling point
	(D) 5		(D) None of these
	Space For	Rough \	Work

- 51. A solution is made by dissolving 1 kilo mole of solute in 2000 kg of solvent. The molality of the solution is
 - (A) 2
 - (B) 1
 - (C) 0.5
 - (D) 1.5
- 52. If 1.5 moles of oxygen combines with aluminium to form Al₂O₃, then the weight of aluminium (atomic weight = 27) used in this reaction is
 - (A) 27
 - (B) 54
 - (C) 5.4
 - (D) 2.7

- 53. A solution of specific gravity 1 consists of 35% A by weight and the remaining B. If the specific gravity of A is 0.7, the specific gravity of B is
 - (A) 1.25
 - (B) 1.3
 - (C) 1.35
 - (D) 1.2
- 54. If reciprocating pump having a mechanical efficiency of 80% delivers water at the rate of 80 kg/s with a head of 30 m, the brake power of the pump is kW.
 - (A) 29.4
 - (B) 20.8
 - (C) 15.4
 - (D) 10.8

- 55. For a maximum transmission of power through a pipeline with total head 'H', the head loss due to friction h_f, is given by
 - (A) 0.1H
 - (B) H/3
 - (C) H/2
 - (D) 2H/3
- 56. To produce talcum powder, use
 - (A) Ball mill
 - (B) Hammer mill
 - (C) Jet mill
 - (D) Pin mil
- 57. The terminal settling velocity of a 6 mm diameter glass sphere (density: 2500 kg/m³) in a viscous Newtonian liquid (density: 1500 kg/m³) is 100 μm/s. If the particle Reynolds number is small and the value of acceleration due to gravity is 9.81 m/s², then the viscosity of the liquid (in Pa.s) is
 - (A) 100
 - (B) 196.2
 - (C) 245.3
 - (D) 490.5

- 58. For a particle settling in water at its terminal settling velocity, which of the following is true?
 - (A) Buoyancy = weight + drag
 - (B) Weight = buoyancy + drag
 - (C) Drag = buoyancy + drag
 - (D) Drag = weight
- 59. Thermal radiative flux from a surface of emissivity 0.4 is 22.68 kW/m². The approximate surface temperature (K) is (Stefan-Boltzman constant = 5.67 × 10⁻⁸ W/m².K⁴)
 - (A) 1000
 - (B) 727
 - (C) 800
 - (D) 1200
- 60. A multiple effect evaporator has a capacity to process 4000 kg of solid caustic soda per day, when it is concentrating from 10% to 25 % solids. The water evaporated in kg per day is
 - (A) 6000
 - (B) 24000
 - (C) 60000
 - (D) 48000

- 61. A 2 ton air-conditioner installed in a room and working continuously for 2 hours will remove heat of kcal.
 - (A) 12096
 - (B) 6084
 - (C) 3024
 - (D) 1296
- 62. If 30,000 kcal/hr of heat is removed from a room, then the refrigeration tonnage will be nearly equal to tons of refrigeration.
 - (A) 5
 - (B) 10
 - (C) 20
 - (D) 30
- 63. $C_p C_v = R$ is valid for _____ gases.
 - (A) Ideal
 - (B) All
 - (C) Very high pressure
 - (D) Very low pressure

- does not depend upon reaction time, extent of reaction and the initial concentration of reactants; but it is a function of reaction temperature. In a chemical reaction, the time required to reduce the concentration of reactant from 100 gm moles/litre to 50 gm moles/litre is same as that required to reduce it from 2 gm moles/litre to 1 gm mole/litre in the same volume. Then the order of this reaction is
 - (A) 0
 - (B) 1
 - (C) 2
 - (D) 3
- 65. The conversion for a first order liquid phase reaction. A → B in a CSTR is 50%. If another CSTR of the same volume is connected in series, then the conversion % at the exit of the second reactor will be
 - (A) 60
 - (B) 75
 - (C) 90
 - (D) 100

- 66. Which of the following will give maximum gas conversion?
 - (A) Fixed bed reactor
 - (B) Fluidised bed reactor
 - (C) Semi-Fluidised bed reactor
 - (D) Plug-flow catalytic reactor
- 67. The time constant of a first order process with resistance R and capacitance C is
 - (A) R+C
 - (B) R-C
 - (C) RC
 - (D) 1/RC

- 68. Identify an unbounded input from inputs whose transfer functions are given below.
 - (A) 1
 - (B) 1/S
 - (C) $1/S^2$
 - (D) $1/(S^2+1)$
- 69. In a feed-back control system G and H
 denote open loop and close loop
 transfer functions respectively. The
 output-input relationship is
 - (A) G/1+H
 - (B) H/1+G
 - (C) G/H
 - (D) H/G

70.	BOD of raw municipal sewage may be	73.	For turbulent mass transfer in pipes,	
	in the range of about mg/litre.		the Sherwood number depends on the	
	(A) 1-2		Reynolds number as	
	(B) 5-10		(A) Re ^{0.33}	
	(C) 150-300		(B) Re ^{0.83}	
	(D) 2000-3000		(C) $Re^{0.53}$	
			(D) Re	
71.	COD of raw municipal sewage may be in the range of about mg/litre.	74.	Solvay process is used for the	
			manufacture of	
	(A) 1-2		(A) Caustic soda	
	(B) 5-10		(B) Soda ash	
	(C) 90-120		(C) Caustic potash	
	(D) 1500-2500		(D) Soda lime	
72.	Molecular diffusivity of a liquid	75.	Styrene is produced from ethyl	
	(A) increases with temperature.		benzene by the process of	
	(B) decreases with temperature.		(A) Dehydrogenation	
			(B) Oxidation	
	(C) may increase or decrease with temperature.		(C) Alkylation	
	(D) is independent of temperature.		(D) Dehydration	
	Space For Rough Work			