

Sample Question Paper
Class: XII Session: 2021-22
Computer Science (Code 083)
(Theory: Term-1)

Maximum Marks: 35

Time Allowed: 90 Minutes

General Instructions:

- The question paper is divided into 3 Sections - A, B and C.
- Section A, consist of 25 Questions (1-25). Attempt any 20 questions.
- Section B, consist of 24 Questions (26-49). Attempt any 20 questions.
- Section C, consist of 6 case study based Questions (50-55). Attempt any 5 questions.
- All questions carry equal marks.

Q.N.	Section-A
	This section consists of 25 Questions (1 to 25). Attempt any 20 questions from this section. Choose the best possible option.
1	Find the invalid identifier from the following a. none b. address c. Name d. pass
2	Consider a declaration L = (1, 'Python', '3.14'). Which of the following represents the data type of L? a. list b. tuple c. dictionary d. string
3	Given a Tuple tup1= (10, 20, 30, 40, 50, 60, 70, 80, 90). What will be the output of print (tup1 [3:7:2])? a. (40,50,60,70,80) b. (40,50,60,70) c. [40,60] d. (40,60)
4	Which of the following option is not correct? a. if we try to read a text file that does not exist, an error occurs. b. if we try to read a text file that does not exist, the file gets created. c. if we try to write on a text file that does not exist, no error occurs. d. if we try to write on a text file that does not exist, the file gets Created.
5	Which of the following options can be used to read the first line of a text file Myfile.txt? a. myfile = open('Myfile.txt'); myfile.read() b. myfile = open('Myfile.txt','r'); myfile.read(n) c. myfile = open('Myfile.txt'); myfile.readline() d. myfile = open('Myfile.txt'); myfile.readlines()

6	<p>Assume that the position of the file pointer is at the beginning of 3rd line in a text file. Which of the following option can be used to read all the remaining lines?</p> <ul style="list-style-type: none">a. <code>myfile.read()</code>b. <code>myfile.read(n)</code>c. <code>myfile.readline()</code>d. <code>myfile.readlines()</code>
7	<p>A text file <code>student.txt</code> is stored in the storage device. Identify the correct option out of the following options to open the file in read mode.</p> <ul style="list-style-type: none">i. <code>myfile = open('student.txt','rb')</code>ii. <code>myfile = open('student.txt','w')</code>iii. <code>myfile = open('student.txt','r')</code>iv. <code>myfile = open('student.txt')</code> <ul style="list-style-type: none">a. only ib. both i and ivc. both iii and ivd. both i and iii
8	<p>The return type of the <code>input()</code> function is</p> <ul style="list-style-type: none">a. stringb. integerc. listd. tuple
9	<p>Which of the following operator cannot be used with string data type?</p> <ul style="list-style-type: none">a. +b. inc. *d. /
10	<p>Consider a tuple <code>tup1 = (10, 15, 25, and 30)</code>. Identify the statement that will result in an error.</p> <ul style="list-style-type: none">a. <code>print(tup1[2])</code>b. <code>tup1[2] = 20</code>c. <code>print(min(tup1))</code>d. <code>print(len(tup1))</code>
11	<p>Which of the following statement is incorrect in the context of binary files?</p> <ul style="list-style-type: none">a. Information is stored in the same format in which the information is held in memory.b. No character translation takes placec. Every line ends with a new line characterd. pickle module is used for reading and writing
12	<p>What is the significance of the <code>tell()</code> method?</p> <ul style="list-style-type: none">a. tells the path of fileb. tells the current position of the file pointer within the filec. tells the end position within the filed. checks the existence of a file at the desired location

13	<p>Which of the following statement is true?</p> <ul style="list-style-type: none"> a. pickling creates an object from a sequence of bytes b. pickling is used for object serialization c. pickling is used for object deserialization d. pickling is used to manage all types of files in Python
14	<p>Syntax of seek function in Python is <code>myfile.seek(offset, reference_point)</code> where <code>myfile</code> is the file object. What is the default value of <code>reference_point</code>?</p> <ul style="list-style-type: none"> a. 0 b. 1 c. 2 d. 3
15	<p>Which of the following components are part of a function header in Python?</p> <ul style="list-style-type: none"> a. Function Name b. Return Statement c. Parameter List d. Both a and c
16	<p>Which of the following function header is correct?</p> <ul style="list-style-type: none"> a. <code>def cal_si(p=100, r, t=2)</code> b. <code>def cal_si(p=100, r=8, t)</code> c. <code>def cal_si(p, r=8, t)</code> d. <code>def cal_si(p, r=8, t=2)</code>
17	<p>Which of the following is the correct way to call a function?</p> <ul style="list-style-type: none"> a. <code>my_func()</code> b. <code>def my_func()</code> c. <code>return my_func</code> d. <code>call my_func()</code>
18	<p>Which of the following character acts as default delimiter in a csv file?</p> <ul style="list-style-type: none"> a. (colon) : b. (hyphen) - c. (comma) , d. (vertical line)
19	<p>Syntax for opening Student.csv file in write mode is <code>myfile = open("Student.csv","w",newline=")</code>.</p> <p>What is the importance of <code>newline=""</code>?</p> <ul style="list-style-type: none"> a. A newline gets added to the file b. Empty string gets appended to the first line. c. Empty string gets appended to all lines. d. EOL translation is suppressed
20	<p>What is the correct expansion of CSV files?</p> <ul style="list-style-type: none"> a. Comma Separable Values b. Comma Separated Values c. Comma Split Values d. Comma Separation Values

21	<p>Which of the following is not a function / method of csv module in Python?</p> <ul style="list-style-type: none"> a. read() b. reader() c. writer() d. writerow()
22	<p>Which one of the following is the default extension of a Python file?</p> <ul style="list-style-type: none"> a. .exe b. .p++ c. .py d. .p
23	<p>Which of the following symbol is used in Python for single line comment?</p> <ul style="list-style-type: none"> a. / b. /* c. // d. #
24	<p>Which of the following statement opens a binary file record.bin in write mode and writes data from a list lst1 = [1,2,3,4] on the binary file?</p> <ul style="list-style-type: none"> a. with open('record.bin','wb') as myfile: pickle.dump(lst1,myfile) b. with open('record.bin','wb') as myfile: pickle.dump(myfile,lst1) c. with open('record.bin','wb+') as myfile: pickle.dump(myfile,lst1) d. with open('record.bin','ab') as myfile: pickle.dump(myfile,lst1)
25	<p>Which of these about a dictionary is false?</p> <ul style="list-style-type: none"> a) The values of a dictionary can be accessed using keys b) The keys of a dictionary can be accessed using values c) Dictionaries aren't ordered d) Dictionaries are mutable
Section-B	
This section consists of 24 Questions (26 to 49). Attempt any 20 questions.	
26	<p>What is the output of following code:</p> <pre style="margin-left: 40px;">T=(100) print(T*2)</pre> <ul style="list-style-type: none"> a. Syntax error b. (200,) c. 200 d. (100,100)

27	<p>Suppose content of 'Myfile.txt' is:</p> <div style="border: 1px solid black; padding: 5px; margin: 10px auto; width: fit-content;"><p>Twinkle twinkle little star How I wonder what you are Up above the world so high Like a diamond in the sky</p></div> <p>What will be the output of the following code?</p> <pre>myfile = open("Myfile.txt") data = myfile.readlines() print(len(data)) myfile.close()</pre> <p>a. 3 b. 4 c. 5 d. 6</p>
28	<p>Identify the output of the following Python statements.</p> <pre>x = [[10.0, 11.0, 12.0],[13.0, 14.0, 15.0]] y = x[1][2] print(y)</pre> <p>a. 12.0 b. 13.0 c. 14.0 d. 15.0</p>
29	<p>Identify the output of the following Python statements.</p> <pre>x = 2 while x < 9: print(x, end='') x = x + 1</pre> <p>a. 12345678 b. 123456789 c. 2345678 d. 23456789</p>
30	<p>Identify the output of the following Python statements.</p> <pre>b = 1 for a in range(1, 10, 2): b += a + 2 print(b)</pre> <p>a. 31 b. 33 c. 36 d. 39</p>

31	<p>Identify the output of the following Python statements.</p> <pre>lst1 = [10, 15, 20, 25, 30] lst1.insert(3, 4) lst1.insert(2, 3) print (lst1[-5])</pre> <p>a. 2 b. 3 c. 4 d. 20</p>																		
32	<p>Raghav is trying to write a tuple tup1 = (1,2,3,4,5) on a binary file test.bin. Consider the following code written by him.</p> <pre>import pickle tup1 = (1,2,3,4,5) myfile = open("test.bin",'wb') pickle._____ #Statement 1 myfile.close()</pre> <p>Identify the missing code in Statement 1.</p> <p>a. dump(myfile,tup1) b. dump(tup1, myfile) c. write(tup1,myfile) d. load(myfile,tup1)</p>																		
33	<p>A binary file employee.dat has following data</p> <table border="1" data-bbox="625 1018 1096 1281"> <thead> <tr> <th>Empno</th> <th>empname</th> <th>Salary</th> </tr> </thead> <tbody> <tr> <td>101</td> <td>Anuj</td> <td>50000</td> </tr> <tr> <td>102</td> <td>Arijita</td> <td>40000</td> </tr> <tr> <td>103</td> <td>Hanika</td> <td>30000</td> </tr> <tr> <td>104</td> <td>Firoz</td> <td>60000</td> </tr> <tr> <td>105</td> <td>Vijaylakshmi</td> <td>40000</td> </tr> </tbody> </table> <pre>def display(eno): f=open("employee.dat","rb") totSum=0 try: while True: R=pickle.load(f) if R[0]==eno: _____ #Line1 totSum=totSum+R[2] except: f.close() print(totSum)</pre> <p>When the above mentioned function, display (103) is executed, the output displayed is 190000.</p> <p>Write appropriate jump statement from the following to obtain the above output.</p>	Empno	empname	Salary	101	Anuj	50000	102	Arijita	40000	103	Hanika	30000	104	Firoz	60000	105	Vijaylakshmi	40000
Empno	empname	Salary																	
101	Anuj	50000																	
102	Arijita	40000																	
103	Hanika	30000																	
104	Firoz	60000																	
105	Vijaylakshmi	40000																	

	<ul style="list-style-type: none"> a. jump b. break c. continue d. return
34	<p>What will be the output of the following Python code?</p> <pre>def add (num1, num2): sum = num1 + num2 sum = add(20,30) print(sum)</pre> <ul style="list-style-type: none"> a. 50 b. 0 c. Null d. None
35	<p>Evaluate the following expression and identify the correct answer.</p> $16 - (4 + 2) * 5 + 2**3 * 4$ <ul style="list-style-type: none"> a. 54 b. 46 c. 18 d. 32
36	<p>What will be the output of the following code?</p> <pre>def my_func(var1=100, var2=200): var1+=10 var2 = var2 - 10 return var1+var2 print(my_func(50),my_func())</pre> <ul style="list-style-type: none"> a. 100 200 b. 150 300 c. 250 75 d. 250 300
37	<p>What will be the output of the following code?</p> <pre>value = 50 def display(N): global value value = 25 if N%7==0: value = value + N else: value = value - N print(value, end="#") display(20) print(value)</pre> <ul style="list-style-type: none"> a. 50#50 b. 50#5 c. 50#30 d. 5#50#

38	<p>What will be the output of the following code?</p> <pre>import random List=["Delhi", "Mumbai", "Chennai", "Kolkata"] for y in range(4): x = random.randint(1, 3) print(List[x], end="#")</pre> <p>a. Delhi#Mumbai#Chennai#Kolkata# b. Mumbai#Chennai#Kolkata#Mumbai# c. Mumbai# Mumbai #Mumbai # Delhi# d. Mumbai# Mumbai #Chennai # Mumbai</p>
39	<p>What is the output of the following code snippet?</p> <pre>def ChangeVal(M,N): for i in range(N): if M[i]%5 == 0: M[i]//=5 if M[i]%3 == 0: M[i]//=3 L = [25, 8, 75, 12] ChangeVal(L, 4) for i in L: print(i, end="#")</pre> <p>a) 5#8#15#4# b) 5#8#5#4# c) 5#8#15#14# d) 5#18#15#4#</p>
40	<p>Suppose content of 'Myfile.txt' is</p> <div style="border: 1px solid black; padding: 5px; margin: 10px auto; width: fit-content;"> <p>Humpty Dumpty sat on a wall Humpty Dumpty had a great fall All the king's horses and all the king's men Couldn't put Humpty together again</p> </div> <p>What will be the output of the following code?</p> <pre>myfile = open("Myfile.txt") record = myfile.read().split() print(len(record)) myfile.close()</pre> <p>a. 24 b. 25 c. 26 d. 27</p>
41	<p>Find the output of the following code:</p> <pre>Name="Python3.1" R="" for x in range(len(Name)): if Name[x].isupper(): R=R+Name[x].lower()</pre>


```

elif Name[x].islower():
    R=R+Name[x].upper()
elif Name[x].isdigit():
    R=R+Name[x-1]
else:
    R=R+"#"
print(R)

```

- a. pYTHOn##@
- b. pYTHOnN#@
- c. pYTHOn#@
- d. pYTHOnN@#

42 Suppose content of 'Myfile.txt' is

Honesty is the best policy.

What will be the output of the following code?

```

myfile = open("Myfile.txt")
x = myfile.read()
print(len(x))
myfile.close()

```

- a. 5
- b. 25
- c. 26
- d. 27

43 Suppose content of 'Myfile.txt' is

Culture is the widening of the mind and of the spirit.

What will be the output of the following code?

```

myfile = open("Myfile.txt")
x = myfile.read()
y = x.count('the')
print(y)
myfile.close()

```

- a. 2
- b. 3
- c. 4
- d. 5

44 What will be the output of the following code?

```

x = 3
def myfunc():
    global x
    x+=2
    print(x, end=' ')
print(x, end=' ')
myfunc()
print(x, end=' ')

```

- a. 3 3 3
- b. 3 4 5
- c. 3 3 5
- d. 3 5 5

45

Suppose content of 'Myfile.txt' is

```
Ek Bharat Shreshtha Bharat
```

What will be the output of the following code?

```
myfile = open("Myfile.txt")
vlist = list("aeiouAEIOU")
vc=0
x = myfile.read()
for y in x:
    if(y in vlist):
        vc+=1
print(vc)
myfile.close()
```

- a. 6
- b. 7
- c. 8
- d. 9

46

Suppose content of 'Myfile.txt' is

```
Twinkle twinkle little star
How I wonder what you are
Up above the world so high
Like a diamond in the sky
Twinkle twinkle little star
```


What will be the output of the following code?

```
myfile = open("Myfile.txt")
line_count = 0
data = myfile.readlines()
for line in data:
    if line[0] == 'T':
        line_count += 1
print(line_count)
myfile.close()
```

- a. 2
- b. 3
- c. 4
- d. 5

47

Consider the following directory structure.



Suppose root directory (School) and present working directory are the same. What will be the absolute path of the file Syllabus.jpg?

- School/syllabus.jpg
- School/Academics/syllabus.jpg
- School/Academics/./syllabus.jpg
- School/Examination/syllabus.jpg

48

Assume the content of text file, 'student.txt' is:

```

Arjun Kumar
Ismail Khan
Joseph B
Hanika Kiran
  
```

What will be the data type of data_rec?

```

myfile = open("Myfile.txt")
data_rec = myfile.readlines()
myfile.close()
  
```

- string
- list
- tuple
- dictionary

49

What will be the output of the following code?

```

tup1 = (1,2,[1,2],3)
tup1[2][1]=3.14
print(tup1)
  
```

- (1,2,[3.14,2],3)
- (1,2,[1,3.14],3)
- (1,2,[1,2],3.14)
- Error Message

Section-C
Case Study based Questions

This section consists of 6 Questions (50 -55) Attempt any 5 questions.

Rohit, a student of class 12, is learning CSV File Module in Python. During examination, he has been assigned an incomplete python code (shown below) to create a CSV File 'Student.csv' (content shown below). Help him in completing the code which creates the desired CSV File.

CSV File

```
1,AKSHAY,XII,A
2,ABHISHEK,XII,A
3,ARVIND,XII,A
4,RAVI,XII,A
5,ASHISH,XII,A
```

Incomplete Code

```
import _____ #Statement-1
fh = open(_____, _____, newline="") #Statement-2
stuwriter = csv._____ #Statement-3
data = [ ]
header = ['ROLL_NO', 'NAME', 'CLASS', 'SECTION']
data.append(header)
for i in range(5):
    roll_no = int(input("Enter Roll Number : "))
    name = input("Enter Name : ")
    Class = input("Enter Class : ")
    section = input("Enter Section : ")
    rec = [ _____ ] #Statement-4
    data.append(_____) #Statement-5
stuwriter. _____ (data) #Statement-6
fh.close()
```

50 Identify the suitable code for blank space in the line marked as Statement-1.

- a) csv file
- b) CSV
- c) csv
- d) cvs

51 Identify the missing code for blank space in line marked as Statement-2.

- a) "Student.csv","wb"
- b) "Student.csv","w"
- c) "Student.csv","r"
- d) "Student.cvs","r"

52 Choose the function name (with argument) that should be used in the blank space of line marked as Statement-3.

- a) reader(fh)
- b) reader(MyFile)
- c) writer(fh)
- d) writer(MyFile)

53	<p>Identify the suitable code for blank space in line marked as Statement-4.</p> <ul style="list-style-type: none">a) 'ROLL_NO', 'NAME', 'CLASS', 'SECTION'b) ROLL_NO, NAME, CLASS, SECTIONc) 'roll_no','name','Class','section'd) roll_no,name,Class,section
54	<p>Identify the suitable code for blank space in the line marked as Statement-5.</p> <ul style="list-style-type: none">a) datab) recordc) recd) insert
55	<p>Choose the function name that should be used in the blank space of line marked as Statement-6 to create the desired CSV File?</p> <ul style="list-style-type: none">a) dump()b) load()c) writerows()d) writerow()